

Crimped Woven Wire Mesh Specifications

lightweight
(Rolls)

Wire Diameter (mm)	Mesh Opening (mm)	Mesh Opening (inch)	Width (m)	Roll Length (m)
0.8 - 1.0	3 × 3	1/8"	0.9 - 1.5	20 - 30
1.0 - 1.2	4 × 4	5/32"	0.9 - 1.5	20 - 30
1.2 - 1.4	5 × 5	3/16"	0.9 - 1.5	20 - 30
1.5 - 1.8	6 × 6	1/4"	0.9 - 1.5	20 - 30
1.8 - 2.0	8 × 8	5/16"	0.9 - 1.5	20 - 30
2.0 - 2.2	10 × 10	3/8"	0.9 - 1.5	20 - 30

heavy-duty
(Panels)

Wire Diameter (mm)	Mesh Opening (mm)	Mesh Opening (inch)	Width (m)	Panel Length (m)
2.0 - 3.0	12 × 12	1/2"	1.0 - 2.0	2.0 - 2.4
3.0 - 3.5	15 × 15	5/8"	1.0 - 2.0	2.0 - 2.4
3.2 - 4.0	20 × 20	3/4"	1.0 - 2.0	2.0 - 2.4
4.0 - 5.0	25 × 25	1"	1.0 - 2.0	2.0 - 2.4
5.0 - 6.0	30 × 30	1-3/16"	1.0 - 2.0	2.0 - 2.4
6.0 - 8.0	50 × 50	2"	1.0 - 2.0	2.0 - 2.4

Notes

Crimp Types: Double Crimp (DC), Intermediate Crimp (IC), Lock Crimp (LC), Flat Top (FT). Specify when ordering.

Materials: Low carbon steel wire, galvanized steel wire, stainless steel wire (304 / 316). Available in black wire, electro galvanized, hot-dipped galvanized, or stainless steel finish.