

Dutch Weave Wire Mesh Specifications

Mesh Count (warp × weft)	Wire Diameter (mm)	Thickness (mm)	Filter Rating (μm)	Material
24 × 110	0.36 / 0.25	0.63	280 - 300	SS304 / SS316
30 × 150	0.25 / 0.20	0.45	180 - 200	SS304 / SS316
40 × 200	0.20 / 0.16	0.36	120 - 150	SS304 / SS316
50 × 250	0.14 / 0.11	0.26	100 - 120	SS304 / SS316
60 × 300	0.12 / 0.09	0.22	70 - 90	SS304 / SS316
80 × 400	0.10 / 0.07	0.2	60 - 80	SS304 / SS316
100 × 600	0.07 / 0.05	0.17	40 - 60	SS304 / SS316
120 × 900	0.09 / 0.05	0.23	55 - 60	SS304 / SS316
150 × 1000	0.07 / 0.045	0.2	40 - 45	SS304 / SS316
200 × 1400	0.05 / 0.035	0.16	25 - 30	SS304 / SS316
325 × 2300	0.035 / 0.025	0.11	10 - 15	SS304 / SS316
400 × 2800	0.030 / 0.020	0.09	8 - 10	SS304 / SS316

material: 304/316/And special stainless steel
Weaving method: plain weave/Twill weave/Dutch weave
Special specifications can be customized
All specifications comply with ASTM E2016 standards.